




IdeaPad Yoga 13 Keyboard Bezel Replacement

Remove your laptop's keyboard bezel to replace it if damaged or access interior components.

Written By: Remington Jones



INTRODUCTION

The keyboard bezel is part of the chassis that protects your laptop's interior components. Cosmetic damage may be unsightly, but doesn't affect your laptop's functionality. You may need to remove the keyboard bezel to access interior components.



TOOLS:

- [iFixit Opening Tools](#) (1)
 - [Tweezers](#) (1)
 - [Phillips #0 Screwdriver](#) (1)
 - [Metal Spudger](#) (1)
-

Step 1 — Keyboard




- ❗ Power off your laptop before beginning disassembly.
- Open the laptop to locate the keyboard.

Step 2




- Insert a plastic opening tool in the seam between the keyboard and laptop body.
- Carefully run the tool around the top and sides of the keyboard to pop out the 9 tabs holding in the keyboard.


Step 3



- Lift the keyboard up, then pivot it towards you to lay it facedown on the trackpad and palm rests.

 Be careful when lifting the keyboard up. The ribbon cable connecting it to the motherboard is very short, and the connector is fragile.

Step 4




- Locate the ribbon cable connecting the keyboard to the motherboard.
- Use the tip of the opening tool to lift the black flap on the connector.
- With the tweezers, gently lift the ribbon cable out of the connector.

 Be careful when reinserting the ribbon cable.


- Ensure the cutouts on the end of the cable match the tabs on the connector.

Step 5 — Keyboard Bezel





- Locate and remove the screws holding the bezel to the laptop body:
 - Two 3 mm Phillips screws
 - Three 5.5 mm Phillips screws


Step 6




- Flip the laptop over.
- Locate and remove the screws holding the bezel to the bottom panel:
 - Ten 4.5 mm Phillips screws


Step 7



 There is now nothing securing the bezel to the laptop body. However, there are still two cables connecting the bezel to the mainboard. Ensure the bezel remains in place until the cables are disconnected.


- Flip the laptop back over.
 - Locate the small trackpad ribbon cable and use the opening tool to lift the black flap on the connector.
 - With tweezers, gently pull the ribbon cable out of the connector.
-  You can use the clear plastic tab on the top of the ribbon connector to help pull the cable out.

Step 8



- Locate the power board cable and disconnect it by pulling the cable head towards the front of the laptop.
- ⓘ You can use a metal spudger to push the head out of the socket.
- ⚠ Be careful to not damage the socket.

Step 9



- Lift the keyboard bezel off the laptop.
- ⓘ You may need to flip the screen around to get the necessary clearance at the hinges.

To reassemble your device, follow these instructions in reverse order.